

SLAC ILC program, International BDS Design, ATF2 facility

Andrei Seryi

May 3, 2005

Seminar at CERN

Contents

- **SLAC ILC program**
 - » following the outline given by Tor Raubenheimer
- **Very exciting strong program addressing most of the design issues**
 - SLAC program addresses 14 of the 15 “R2” items identified by the 2003 TRC report as well as many additional problems
- **Program is focused on overall accelerator design issues as well as a few technology development concepts**
- **International design of the ILC BDS**

SLAC ILC Program

- Program for FY05/FY06 has six main elements
 - Electron and Positron sources
 - Damping rings
 - Beam Delivery System and Interaction Region
 - Overall design: Beam parameters, Optics, Emittance preservation, Stability/alignment, Instrumentation, Availability, MPS, and Operational issues
 - Conventional construction implications and site development
 - Linac rf technology
 - klystrons, modulators, rf distribution, and possibly couplers
 - Wakefields and cavity optimization
 - Not SC Cavity fabrication

System Design


- Extensive simulation of sub-systems
 - Balance emittance budgets and specify system tolerances → impact on overall beam parameters
- Consider operational issues
 - Design for availability and work on detailed models → big impact on layouts and configuration but hard to quantify
 - Develop beam tuning algorithms → specify beam instrumentation requirements and layout
 - Consider high-level controls software requirements (applications) for beam control → specify control system requirements
- Develop Machine Protection Scenarios
 - Specify active and sacrificial protection systems
 - Specify beam dumps and beam tuning stations

Major Test Facilities

- **NLCTA**
 - Complete X-band program
 - Create new L-band rf Test Facility
 - Test klystron and modulators for ILC
 - Test normal conducting structures for e^+/e^- sources
 - Construct coupler test facility
 - Facilities also available in Klystron Test Lab
- **End Station A**
 - Study Interaction Region issues and instrumentation
 - Mockup of full IR
- **ATF-2**
 - Test BDS using very low emittance beam
- Utilize other test facilities around the world (TTF, SMTF, STF, ATF)

UK/US/KEK team at ATF, march 2005

- MB emittance study
- Wiggler study
- High quality beam extraction
- nm resolution BPM test & demonstration
- Fast feedback test & demonstration
- Fast Kicker for ILC damping ring
- Instrumentation developments (LW, XSR monitor, ODR monitor,
- MB-BPM, (SB, MB) longitudinal
- feedback, etc.)
- Preparation of 'ATF-2'



Electron and Positron Source

- Electron source

- Continuing photocathode development
- Creating space to begin laser and gun development


- Positron source (program with LLNL)

- Studying target design for undulator, conventional, and Compton sources
 - Radiation damage
 - Thermal shock / beam damage
 - Engineering issues (high rotation speed, remote handling)
- NC capture structure design and fabrication
- Capture and optics studies
- Complete E-166 polarized positron production (spring 2005)

Damping Rings

- Damping ring design (program with LBNL)
 - Optics and tuning studies
 - Collective effects
 - Bunch compressor design
- SEY Studies (program with LBNL)
 - Laboratory measurements in PEL
 - Building three chambers for PEP-II installation to verify solutions
- ATF at KEK (for DR and BDS)
 - Instrumentation (NanoBPM, laser wires, optical anchor)
 - Beam studies (ORM, BBA, FBII, Wiggler)
 - ATF Kicker replacement
 - ATF stripline kicker development
 - FONT/Feather




Electron Cloud Simulations



Electron density in units of e/m^3 as a function of time for an arc bend in the 6km DR option assuming a beam pipe radius 22mm and including an antechamber design (full height $h=10\text{mm}$).

SEY Studies in PEP LER

- Building test inserts chambers for PEP-II
 - test chamber with coated samples
 - Two 'grooved' chambers to verify a proposal by Mauro Pivi and Gennady Stupakov



Linac Design

- **Quadrupole alignment**
 - Use a SC linac quadrupole from DESY to study shunting alignment ability – very important to achieve desired tolerances
 - Continue program for NC quadrupoles
- **BPM tests (program with TTF, ATF and LCLS)**
 - Develop and test high resolution BPMs
- **Cavity diagnostics (program at TTF)**
 - Add HOM detectors to SC cavities at TTF to determine beam-cavity location – very important especially for high shunt impedance cavities with small aperture
- **Measure vibration due to SC cryogenic equipment**
 - Important for conventional layout and BDIR



Superconducting Quadrupole

- Goal—Demonstrate Linac Quad/BPM performance required for ILC
 - Verify ~ 5 micron stability of quad magnetic center
 - Show ~ 1 micron BPM resolution and $< \sim 5$ micron quad-to-bpm stability in compact, 80 mm aperture design.
- Approach—Test TESLA prototype quad built by CIEMAT in Spain and BPM developed at SLAC
- Plan—Build cryostat for prototype quad and test at Magnetic Measurements Lab with rotating coil. Do beam tests of BPM and eventually integrate quad and BPM for test in LI02




Cavity HOM Measurements

- Understanding HOM signals from TTF
 - Instrumentation used to measure HOMs in the TTF cavities
 - Analysis was complicated because timing system was noisy
 - Seem to achieve resolutions at the 16 micron level
 - Questions about relative alignment of modes
 - Potential to be very useful



Wakefield Calculations

- Extensive 3-D modeling of the TESLA and the new Low-Loss SC cavity wakefields
 - Big computation: 768 processors and requires 300 GB memory
 - Mode rotation may be an important source of jitter
 - Need to understand if this is mostly systematic due to the coupler orientation or due to fabrication errors
 - Huge effect if it is systematic



- New Low Loss cavities have lower cryoloads but higher wakes
 - Big impact on design → may make 35 or 40 MV/m possible
 - Need to understand the wakefield implications

Modulators

- ILC baseline modulator was developed in the early 90's at FermiLab for use with the TTF
- Advantages:
 - Simple circuit topology
 - Proven design; 10+ years of operation



Disadvantages:

- High stored energy – 270kJ
 - Massive pulse transformer – 6.5 tons
 - Single-point failures can damage klystron
 - Requires large floor area
 - Insulating oil – 100's of gallons
- SLAC effort is evaluating options, e.g.
 - Marx generator style which should provide similar efficiency and 100% availability




Marx Generator Modulator

- Stack of 12 kV units
- Pros
 - Uses emerging technology
 - Modular design for longer MTBF and shorter MTTR
 - No oil; compact unit
 - No magnetic core
 - Finer waveform control
- Cons
 - Uses emerging technology
 - IGBT controls floats at high voltage during the pulse
 - DC power flow must be isolated
 - Timing signals must cross high voltage gradients



Klystrons

- Three industrial vendors for 'baseline' 10MW MBK tubes
 - Still very little real experience with multi-beam klystrons
- Develop L-band sheet beam klystron
 - an alternate to the MBK tubes → significant cost reduction
 - High efficiency design using flat beams instead of 6 beamlets
 - Smaller with simpler focusing, cavities, and cathodes
- Study klystron / modulator options
 - More conservative 5MW tube or lower power PPM tubes
 - Decide which (if any) of these to pursue further





End Station B Program

- Complete X-band program at NLCTA
 - Test CERN structure and other gradient studies
 - Test active switching technology
 - Expect to decommission 8-pac modulator this year
- Start construction of an L-band test facility
- Create facility to construct prototype collimators for the LHC
 - Adaptation of NLC consumable collimator technology to allow the LHC to reach design luminosity
- Support E-163 laser acceleration experiment

ESB L-Band Test Facility

- Build L-band test facility in ESB
 - Test modulators and klystrons
 - Test NC accelerator structures and couplers





ESB L-Band Test Facility

- Modulator will be delivered from SNS this summer
- Scrounging klystron parts from SDI/Anthrax/etc programs
- Buying 5 MW tube from Thales (1 year delivery)





Normal Conducting Structure

- Proposed Structure Design for Positron Source with Mechanical Simplicity, effective cooling and Low Pulsed Heating:
 - e⁺ capture: heating 5kW/cell due to RF & 7.5kW/cell due to particle losses
- Working Progress:
 - Preliminary electrical and cooling design
 - Ready to start mechanical design
 - Will build 5 cell cavity and operate at NLCTA with 5MW source




Work on LHC collimation

- Create facility to construct prototype collimators for the LHC
 - Adaptation of NLC consumable collimator technology to allow the LHC to reach design luminosity



End Station A

- Significant international interest
 - BDS & MDI instrumentation studies, collimator wakefield studies
 - Construct IR mock-up



International design of BDS


- Daresbury, RHUL, QMUL, Oxford, UCL, LAL, CEA/Saclay, CERN, BINP, DESY, INFN, ...
 - KEK, Tokyo University, Kyoto ICR, IHEP, Pohang AL, ...
 - SLAC, BNL, Fermilab, LLNL, Universities, ... and many other ...
 - Truly international efforts
 - Organization, communication and coherency of efforts is improving
 - Estimation > 100 people are involved in machine and machine-detector aspects of BDS
-
- Arriving to baseline configuration at the end of 2005 require better organization of existing efforts
 - Producing CDR with cost at the end of 2006 require increase of engineering support

Stages of BDS design toward CDR


- Present stage: From concepts to optics & from boxes on the layout to Geant models
 - The goal is to mostly finish with this before Snowmass
- Next stage: Performance studies and small optimization of the design & DR to IP studies for the machine & machine-detector performance studies
 - One iteration of such studies should be done before end of 2005
 - impact of parameters (nominal, high luminosity, etc.) on performance
 - finalize baseline configuration at the end of 2005
 - Ongoing engineering design & test will continue and mature
 - Detailed specs for engineering studies
- Third stage: Detailed engineering design; Beam tests; Detector components tests; Civil studies and design; Cost optimization
 - Impact of parameters & options on cost
 - Done during 2006. CDR with cost in Dec.2006


Recommendations from the WG4

Tentative, not frozen configuration, working hypotheses, "strawman"





Strawman configuration is turning into real design






Includes:




- energy spectrometer chicane
- spoilers
- absorbers
- muon shields
- photon masks
- PCs
- stoppers
- instrumentation
- feedback





2mrad IR: from concept to optics



Must Extract on this Side
Otherwise SDO Defocuses
in the Horiz. Plane





IR layout for 2o and 2 mrad with SiD and $L^*=3.5$





- IR layout variations with SiD, Large and Huge detector, optimal L^* , real sizes of FD magnets, etc., need to be studied
 - Implications on detector layout, collimation depth (especially 2mrad), tolerances, background...

2mrad IP Extraction Line in Geant

SLAC-BNL-UK-France
Task Group




Rutherford cable SC
quad and sextupole





Super Septum Quad

Warm Panofsky
septum quad




Compact SC Final Doublet for 20mrad IR: from idea to full engineering design

BNL





QD0 144 T/m

QFEX1 42 T/m




Conceptual Study for Cooling Insertion Magnet of the Linear Collider



3/2/05 K.C. Wu




IR Stability




- Two compact sensors provided to SLAC by PMD/eentec in March 2005 as a results of SBIR program. The size is 5*10*15cm, as requested in specification
- Tests in magnetic field have shown that there is no visible influence of high magnetic field on the MET sensors, so, they can be used as a prototype sensors for the IR region of ILC



Case 4: horizontal anti-parallel
Left: 01124040.ap5 B=0T
Right: 01125133.ap5 B= -1T










Latest achievement: bond the 6-around-1 cable in an even tighter bend radius; down to a bend radius of 3 cable diameters.



BNL




Antisolenoid and DID in SiD





Detailed design of QD0, extraction quad, and antisolenoids

BNL




Detailed comparison of 20mrad and 2mrad IR

20mrad extraction optics



2mrad extraction optics



Extraction line losses, 20 mrad

Ideal collision at IP

| | Total loss, W | Max density (W/m) in SCQ / WQ/ bend/ drift |
|----------------|---------------|--|
| 500 GeV nom. | 0 | 0 / 0 / 0 / 0 |
| 500 GeV high L | 1859 | 1.8 / 49 / 42 / 31 |
| 1 TeV nom. | 187 | 0 / 1.2 / 4.1 / 4.1 |
| 1 TeV high L | 97490 | 496 / 4025 / 2481 / 1352 |

Large vertical offset between beams at IP

| Total loss, W | Max density (W/m) in SCQ / WQ/ bend/ drift |
|---------------|--|
| 4.9 | 0 / 0.42 / 0.12 / 0.43 |
| 13280 | 0 / 308 / 383 / 950 |
| 3384 | 0 / 106 / 79 / 254 |
| 312557 | 559 / 4968 / 8144 / 13101 |

Extraction line losses, 2 mrad (less detailed study)

Ideal collision at IP

| | Loss (W) in QD0/QEXF1/Coll |
|----------------|----------------------------|
| 500 GeV nom. | 0 / 0 / ~20000 |
| 500 GeV high L | ~250 / ~50 / ? |
| 1 TeV nom. | 0 / 0 / ? |
| 1 TeV high L | ? / ? / ? |


Large vertical offset between beams at IP

| Loss (W) in QD0/QEXF1/Coll |
|----------------------------|
| 0 / 0 / ~20000 |
| ~350 / ~400 / ? |
| 0 / 0 / ? |
| ? / ? / ? |

Standard SLAC BSY Copper Protection Collimator Rated at 20 kW


Reference: The Stanford Two-Mile Accelerator, R. Neal, 1968

Figure 20-22 Protection collimator with ion chambers.




Vertical cooling passages drilled on either side of the gap and cooling loops around outside of the body





Collimation and energy deposition studies



ILC-FF9 $\beta_x \cdot \beta_y = 6E5 \text{ m}^2$




Fermilab-SLAC-
UK-DESY



IP



40







Beam parameters

Gamma-gamma with nominal pars.

| | | ILC optimistic | ILC w/ e+e- | NLC $\gamma\gamma$ | e+e- |
|-------------------------------------|--------------------------------|-----------------------|----------------------|----------------------|----------------------|
| f_{rep} | Hz | 5 | 5 | 120 | 5 |
| n_b | | 2820 | 2820 | 95 | 2820 |
| σ_x^*/σ_y^* | mm | 88/4.3 | 175/4.3 | 166/3.0 | 553/5 |
| β_x^*/β_y^* | mm | 1.5/0.3 | 1.5/0.3 | 4/0.08 | 11/0.4 |
| $\varepsilon_{xn}/\varepsilon_{yn}$ | μmrad | 2.5/0.03 | 10/0.03 | 3.6/0.071 | 10/0.03 |
| L_{geom}^{ee} | $\text{cm}^{-2} \text{s}^{-1}$ | 11.8×10^{34} | 5.9×10^{34} | 4.0×10^{34} | 1.6×10^{34} |

•very important that the baseline use standard ILC parameters

Gronberg





- ILC optimistic: tracked = $121\text{nm} * 4.37 \text{ nm}$ (geometrical is $87.6\text{nm} * 4.29\text{nm}$)
- ILC w/e+e- (at beta 3mm/0.3mm): tracked = $323\text{nm} * 5.21\text{nm}$ (geometrical is $247.6\text{nm} * 4.95\text{nm}$)
- Correspondingly, the luminosity with tracked beams are:
- ILC optimistic: $8.48\text{e}+34$ instead of $11.8\text{e}+34$ in the table, i.e. 72%
- ILC w/e+e- : $2.67\text{e}+34$ instead of $5.9\text{e}+34$ in the table, i.e. 45%

ATF-2 at KEK

- ATF-2 would be BDS test
 - Follow-on to FFTB
 - New FFS optics
 - Operational issues

ATF-II-ff LAYOUT



BDS design and ATF-2 facility

- Many reasons to develop the ATF-2
 - Luminosity issues will be extremely challenging in the LC
 - Likely more challenging than achieving the beam energy
 - Complete FFTB studies
 - FFTB never demonstrated routine operation of FFS
 - Need to implement full feedback control and optimization
 - Operate with ILC like bunch train and demonstrate IP feedback
 - Operate with stable low emittance beam from ATF DR
 - Provide demonstration and experience concurrent with ILC construction
 - FFTB experience will be over 15 years old
 - Train new generation of physicists
 - Provide a visible test facility for project reviewers and sponsors

PROPOSAL OF THE NEXT INCARNATION OF ACCELERATOR TEST FACILITY AT KEK FOR THE INTERNATIONAL LINEAR COLLIDER

S. Araki, H. Hayano, Y. Higashi, Y. Honda, K. Kanazawa, K. Kubo, T. Kume, M. Kuriki, S. Kuroda, M. Masuzawa, T. Naito, T. Okugi, R. Sugahara, T. Takahashi, T. Tauchi, N. Terunuma, J. Urakawa, V. Vogel, H. Yamaoka, K. Yokoya, KEK, Ibaraki, J. Gao, W. Liu, G. Pei, J. Wang, IHEP, Beijing, B. Grishanov, P. Logachev, F. Podgorny, V. Telnov, BINP, Novosibirsk, D. Angal-Kalinin, R. Appleby, J. Jones, A. Kalinin, CCLRC, Daresbury, O. Napoly, J. Payet, CEA, Gif-sur-Yvette, H. Braun, D. Schulte, F. Zimmermann, CERN, Geneva, T. Takahashi, Hiroshima University, Y. Iwashita, T. Mihara, Kyoto ICR, P. Bambade, LAL, Orsay, J. Gronberg, LLNL, Livermore, M. Kumada, NIRS, Chiba-shi, S. Danagoulian, S. Mtingwa, North Carolina A&T State University, N. Delerue, D. Howell, A. Reichold, D. Urner, Oxford, J. Choi, J.-Y. Huang, H.S. Kang, E.-S. Kim, S. Kim, I.S. Ko, Pohang Accelerator Laboratory, P. Burrows, G. Christian, S. Molloy, G. White, Queen Mary University of London, I. Agapov, G. Blair, G. Boorman, J. Carter, C. Driouichi, M. Price, Royal Holloway, University of London, N. Walker, DESY, Hamburg, K. Bane, A. Brachmann, T. Himel, T. Markiewicz, J. Nelson, N. Phinney, M. Pivi, T. Raubenheimer, M. Ross, R. Ruland, A. Seryi, C. Spencer, P. Tenenbaum, M. Woodley, SLAC, Stanford, S. Boogert, S. Malton, UCL, London, E. Torrence, University of Oregon, T. Sanuki, T. Suehara, University of Tokyo




Table 1: The achieved ATF beam parameters and the parameters for the ATF2, goals **A** and **B**. The ring energy is $E_0 = 1.28$ GeV, the typical bunch length and energy spread are $\sigma_z \sim 8$ mm and $\Delta E/E = 0.08$ %.

| | Measured | (A) | (B) |
|--|----------|-------|-------|
| Single bunch | | | |
| $N_{bunch} (10^{10})$ | 0.2-1.0 | 0.5 | - |
| DR $\gamma\epsilon_y (10^{-8}\text{m})$ | 1.5 | 3 | - |
| Extr. $\gamma\epsilon_y (10^{-8}\text{m})$ | 3.0-6.5 | 3 | - |
| Multi bunch | | | |
| $N_{bunch} (10^{10})$ | 0.3-0.5 | 0.5 | 0.5 |
| $n_{bunches}$ | 20 | 1-20 | 3-20 |
| DR $\gamma\epsilon_y (10^{-8}\text{m})$ | 3.0-4.5 | 3 | 3 |
| Extr. $\gamma\epsilon_y (10^{-8}\text{m})$ | - | 3 | 3 |
| IP $\sigma_y^* (\text{nm})$ | | 37 | 37 |
| IP $\Delta y/\sigma_y^* (\%)$ | | 30 | 5 |

Configuration with bends to avoid crab-cavity test area

ATF2 Goals & stages:

(A) Small beam size





- (A1) Obtain $\sigma_y \sim 35\text{nm}$
- (A2) Maintain for long time

(B) Stabilization of beam center

- (B1) Down to $< 2\text{nm}$ by nano-BPM
- (B2) Bunch-to-bunch feedback of ILC-like train

As ILC, ATF2 critically depends on instrumentation

- BSM to confirm 35nm beam size
- nano-BPM at IP to see the nm stability
- Laser-wire to tune the beam
- Cavity BPMs to measure the orbit
- Movers, active stabilization, alignment system
- Kickers to produce ILC-like train



Summary

- SLAC ILC program – strong efforts on many fronts
- BDS design is making progress from the concept to optics, from optics to engineering design
- The worldwide BDS group is organizing its work
- There is a lot to do to arrive with a CDR with cost
 - Arriving to baseline configuration at the end of 2005 require better organization of existing efforts
 - Producing CDR with cost at the end of 2006 require increase of engineering support